




MARK I TDR

TORCH & DRILL RESISTANT QUALITY FLOOR SAFE

ALL CMI SAFES COME WITH A FIVE YEAR WARRANTY, EXCLUDING FREIGHT & TRAVELLING, WITH A 12 MONTH WARRANTY ON LOCKS.



- ONE MILLION CHANGE KEYLESS COMBINATION LOCK

- LARGE DOOR OPENING
178mm x 127 (7" x 5")
on hinged door model

- 254mm x 127mm (10" x 5")
on lift-out door model

- Suitable for mounting in floor

- Proven resistance to drilling, oxy-acetylene cutting and explosives

- Relocking devices incorporated in door

- Boltwork activated by Rack & Pinion mechanism preventing opening problems often associated with ordinary floor safes

SUGGESTED INSURABLE CASH RATING FOR MARK I TDR
IN AN UNSUPPORTED (NO ALARMS) DOMESTIC SITUATION IS \$40,000

vortex
locksmiths

(02) 9555 9333


Unit 10, 5-13 Parsons Street
Rozelle NSW 2039

MADE IN AUSTRALIA



MARK I TDR TORCH & DRILL RESISTANT QUALITY FLOOR SAFE

ALL CMI SAFES COME WITH A FIVE YEAR WARRANTY, EXCLUDING FREIGHT & TRAVELLING, WITH A 12 MONTH WARRANTY ON LOCKS.



RECOMMENDED INSTALLATION PROCEDURE

CMI Mark 1 TDR floor safes may be installed in either concrete or timber floors. The opening in floor should be at least 510mm (20") square by 560 deep.

The safe should be secured with a strong mix concrete of at least 40 megapascals (6000 P.S.I.) compressive strength. Steel reinforcing material can also be used to help bond the concrete and provide better security. It is recommended that the mix be poured so that a concrete cover of at least 104mm (4") exists around each side of the safe.

The topping can be brought up to the floor level, but allow about 3mm (1/8") for the lid to fit on to the frame of the safe and finish flush with floor.

In damp situations the concrete should contain a water proofing agent such as "Silasec" or "Yurite" (available from hardware stores). Whilst the concrete is setting the door should be left open for 24 hours.

CMI Safe Co. reserves the right to alter specifications without notice or obligation.

INTERNAL DIMENSIONS (CAPACITY)

MODEL	HEIGHT	WIDTH	DEPTH	WEIGHT	PRICE
TDR 1	305mm	305mm	153mm	32kg	\$
TDR 2	305mm	305mm	229mm	35kg	\$
TDR 3	305mm	305mm	305mm	38kg	\$
TDR 4	381mm	381mm	381mm	48kg	\$

DELIVERY AND INSTALLATION \$

**SUGGESTED INSURABLE CASH RATING FOR MARK I TDR
IN AN UNSUPPORTED (NO ALARMS) DOMESTIC SITUATION IS \$40,000**

**vortex
locksmiths**

(02) 9555 9333

Unit 10, 5-13 Parsons Street
Rozelle NSW 2039

MADE IN AUSTRALIA